

# ME Products Company

"Your Seismic and Expansion Joint Connection"

## Flex Connector Stainless Steel Braided Sch40 Steel Male NPT

Construction: Corrugated Metal Hose and Braid  
Hose: T321 Series Stainless Steel  
Braid: T300 Series Stainless Steel  
End Fittings: Steel Sch40 Male NPT



Model	Size	Offset	OAL	OPR PSIG @70°F	OPR PSIG @250°F	Approx WT. (Lbs.)
1101-050-06.5	1/2"	1/8"	6.50	796	732	.38
1101-050-09.5	1/2"	3/4"	9.50	796	732	.50
1101-050-10	1/2"	3/4"	10.00	796	732	.50
1101-075-07	3/4"	1/8"	7.00	597	549	.50
1101-075-09.5	3/4"	3/4"	9.50	597	549	.75
1101-075-11	3/4"	3/4"	11.00	597	549	.75
1101-075-12	3/4"	3/4"	12.00	597	549	1.0
1101-100-08	1"	1/8"	8.00	455	418	.75
1101-100-11	1"	3/4"	11.00	455	418	1.0
1101-100-12	1"	3/4"	12.00	455	418	1.0
1101-125-08.5	1-1/4"	1/8"	8.50	441	405	1.0
1101-125-13	1-1/4"	3/4"	13.00	441	405	1.3
1101-150-09	1-1/2"	1/8"	9.00	370	340	1.3
1101-150-13.5	1-1/2"	3/4"	13.50	370	340	1.9
1101-150-14	1-1/2"	3/4"	14.00	370	340	1.9
1101-200-10.5	2"	1/8"	10.50	370	340	2.2
1101-200-15	2"	3/4"	15.00	370	340	3.0
1101-200-16	2"	3/4"	16.00	370	340	3.0
1101-250-12	2-1/2"	1/8"	12.00	570	524	4.0
1101-250-16	2-1/2"	3/4"	16.00	570	524	5.0
1101-300-12	3"	1/8"	12.00	450	414	5.0
1101-300-14	3"	1/8"	14.00	450	414	6.6
1101-300-16	3"	3/4"	16.00	450	414	6.6
1101-400-12	4"	1/8"	12.00	285	262	6.8
1101-400-16	4"	1/8"	16.00	285	262	7.5

- For Pulsating Pressure, reduce the working pressure by 50%.
- Custom lengths, stainless steel end fittings and Domestic Assemblies are available upon request.
- Call 760.918.0122 for pricing and details.